# BELDON

## BELDON POS – 2D Industrial Desktop Laser Barcode Scanner

Model No: BN-BSD7060



#### **Price:**

Rs. 38,349

#### Warranty:

- 1 Years(s) manufacturer warranty.
- 1 Year Manufacturer Warranty.

### **Delivery:**

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

#### **Specifications:**

- :Type: BARCODE SCANNER
- :Light Source: Laser
- :Aiming Light / Optical System: Laser aiming line or crosshair
- :Image Sensor: CMOS or Laser Sensor Module
- :CPU / Processor: 32-bit ARM processor or DSP
- :Resolution:  $1280 \times 800$  pixels
- :Print Contrast Ratio: 15% (designed for low-contrast or damaged barcodes)
- :Pitch / Roll / Skew Angle:  $\pm 65^{\circ}/360^{\circ}/\pm 65^{\circ}$
- :Scan Rate: 150
- :Decoding Capability: Extensive 1D & 2D symbologies, including damaged and industrial codes.
- :Indicators: Bright multi-color LEDs
- :Tones/Beeps: Programmable multi-tone beeps
- :Typical Depth Of Field: 50 mm 600 mm
- :Controls / Knobs: Trigger button (optional for desktop), mode switch button, volume adjustment (hardware or software)
- :Display: No
- :Body / Surface Material: ABS Plastic
- :Design: Rugged industrial design with reinforced casing, suited for heavy-duty environments
- :Connectivity / Communication: USB, RS232, industrial Ethernet, optional Bluetooth/Wi-Fi for flexible deployment
- :Technology: Industrial Laser Scanning with 2D Imaging Technology
- :Ideal/Suitable For: Warehouses, factories
- :ESD Protection (Air Discharge): Yes
- :Drop Resistance: 1.8 meters (onto concrete, rugged industrial-grade)
- :Temperature: Operating Temperature: -10°C to 55°C
- :Humidity: 5% to 95% RH
- :Ambient Light: 0 to 100,000 lux
- :Cable: USB/RS232 cable
- :System Interface: USB, RS232, Keyboard Wedge, Industrial Ethernet, optional Bluetooth/Wi-Fi
- :Transmission Distance: Up to 50 meters
- :Bluetooth: Optional, Bluetooth 5.0
- :Communication Mode: Wired (USB, RS232, Industrial Ethernet) and wireless (Bluetooth, Wi-Fi).
- :Power Source: USB powered (5V DC)
- :Voltage: 4.5V to 5.5V DC
- :Battery Charging: Optional
- :Platform / OS: Windows, Mac OS, Linux, Android, iOS (via Bluetooth HID and Industrial Ethernet)
- :Colors: Black
- :Dimensions: 190 mm  $\times$  120 mm  $\times$  115 mm
- :Weight: 1kg

Date: 2025-11-27 06:56