

Dahua 4CH Penta-Brid 1080N/720P Cooper 1U 1HDD WizSense Digital Video Recorder (DH-XVR1B04-I-V2)

Model No: DH-XVR1B04-I-V2







Price:

Rs. 12,000

Warranty:

- 2 Years(s) manufacturer warranty.
- 2 Year Manufacturer Warranty.

Delivery:

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

Specifications:

- :Type: 2 MP, 4 Channel XVR
- :Model: DH-XVR1B04-I
- :Main Processor: Industrial-grade processor
- :Operating System: Embedded Linux
- :Operating Interface: Web; Local GUI
- :SMD Plus Info: 4 channels: Secondary filtering for human and vehicle, reducing false alarms caused by leaves, rain and lighting condition change
- Audio / Video: Analog Camera Input: 4 BNC ports, supports HDCVI/AHD/TVI/CVBS autodetect
- Audio / Video:Camera Input: 1. CVI: 1080p@25/30 fps; 720p@50/60 fps; 720p@25/30 fps. 2. TVI: 1080p@25/30 fps; 720p@25/30 fps. 3. AHD: 1080p@25/30 fps; 720p@25/30 fps.
- Audio / Video:IP Camera Input: Up to 5 channels of IPC access 1 IP channel by default + 4 channels (analog channels are converted to IP channels) Incoming bandwidth: 20 Mbps, recording bandwidth: 20 Mbps and outgoing bandwidth: 20 Mbps *After IP extension is enabled, the AI Function (SMD) will be disabled.
- Audio / Video:Encoding Capacity: Main stream: 1080N/720p/960H/D1/CIF@(1 fps-25/30 fps) Sub stream: CIF@(1 fps-15 fps)
- Audio / Video: Dual-Stream: Yes
- Audio / Video: Video Bit Rate: 32 kbps-4096 kbps
- Audio / Video: Audio Sampling: 8 kHz, 16 bit
- Audio / Video: Audio Bit Rate: 64 kbps
- Audio / Video: Video Output: 1 HDMI, 1 VGA HDMI: 1920 × 1080, 1280 × 1024, 1280 × 720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720
- Audio / Video:Multi-Screen Display: When IP extension mode not enabled: 1/4 When IP extension mode enabled: 1/4/6
- Audio / Video: Third-party Camera Access: Panasonic; Sony; Hanwha; Axis; Arecont; ONVIF
- Compression Standard: Video Compression: AI Coding; Smart H.265+; H.265; Smart H.264+; H.264

- Compression Standard: Audio Compression: G.711a; G.711u; PCM
- Network: Network Protocol: HTTP; HTTPS; TCP/IP; IPv4; IPv6; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; FTP; DDNS; SNMP; Alarm Server; P2P; Auto Registration; IP Search (Supports IP camera, DVR, NVS, etc.)
- Network: Mobile Phone Access: iOS; Android
- Network:Interoperability: ONVIF 22.12 (Profile T; Profile S; Profile G); CGI; SDK
- Network:Browser: Chrome; IE; Safari; Edge; Firefox
- Recording Playback:Record Mode: General; alarm; motion detection
- Recording Playback: Recording Playback: 1/4
- Recording Playback:Backup Method: USB device and network
- Recording Playback: Playback Mode: Instant playback; general playback; event playback; tag playback; smart playback
- Alarm:General Alarm: Motion detection; HDCVI alarm; camera external alarm; network alarm; PIR alarm
- Alarm: Anomaly Alarm: Error (no disk, disk error, low space, low quota space; network disconnection; IP conflict; MAC conflict); video loss; video tampering; camera offline
- Alarm:Intelligent Alarm: SMD Plus
- Alarm: Alarm Linkage: Record; snapshot (panoramic); IPC external alarm output; audio; buzzer; log; preset; email
- Ports: Audio Input: 1-channel RCA 4-channel BNC (Coaxial Audio)
- Ports:Audio Output: 1-channel RCA
- Ports:Two-Way Talk: Yes (share the same audio input with the first channel)
- Ports:HDD Interface: 1 SATA port, up to 6 TB. This limit varies depending on the environment temperature.
- Ports:USB: 2Ports:HDMI: 1
- Ports:VGA: 1
- Ports:Network Port: 1
- General:Power Supply: 12 VDC, 1.5 A
- General:Power Consumption: <7 W (without HDD
- General:Weight: 0.55 kg (1.19 lb)
- General:Dimensions: 197.0 mm \times 203.1 mm \times 41.5 mm (7.76" \times 8.00" \times 1.63") (W \times D \times H)
- General:Operating Temperature: -10 °C to +45 °C (+14 °F to +113 °F)
- General:Storage Temperature: -20 °C to +60 °C (-4 °F to +140 °F)
- General:Installation: Desktop
- General:Certifications: CE-LVD: IEC 62368-1:2014 CE-EMC: EN IEC 61000-3-2:2019, EN 61000-3-3:2013+A1:2019, EN 55032:2015+A11:2020, EN 55035:2017+A11:2020, EN 55024:2010+A1:2015, EN 50130-4:2011+A1:2014
- :Color: Black

Date: 2025-10-31 03:43