



## **Dahua 4CH Penta-Brid 5MP Value/1080P Cooper 1U 1HDD WizSense Digital Video Recorder (DH-XVR1B04H-I)**

Model No: DH-XVR1B04H-I



### **Price:**

---

Rs. 20,390

### **Warranty:**

---

2 Years(s) manufacturer warranty.  
2 Year Manufacturer Warranty.

## **Delivery:**

---

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

## **Specifications:**

---

- :Type: 5 MP, 4 Channel XVR
- :Model: DH-XVR1B04H-I
- :Main Processor: Industrial-grade processor
- :Operating System: Embedded Linux
- :Operating Interface: Web; Local GUI
- :SMD Plus Info: 4 channels: Secondary filtering for human and vehicle, reducing false alarms caused by leaves, rain and lighting condition change
- Audio / Video:Analog Camera Input: 4 BNC ports, supports HDCVI/AHD/TVI/CVBS autodetect
- Audio / Video:Camera Input: 1. CVI: 5 MP@25 fps; 5 MP@20 fps; 5 MP@10/12.5 fps; 4 MP@25/30 fps; 1080p@25/30 fps; 720p@50/60 fps; 720p@25/30fps. 2. TVI: 5 MP@20 fps; 4 MP@25/30 fps; 1080p@25/30 fps; 720p@25/30 fps. 3. AHD: 5 MP@20 fps; 4 MP@25/30 fps; 1080p@25/30 fps; 720p@25/30 fps.
- Audio / Video:IP Camera Input: Up to 6 channels of IPC access 2 IP channels by default + 4 channels (analog channels are converted to IP channels) Incoming bandwidth: 32 Mbps, recording bandwidth: 32 Mbps and outgoing bandwidth: 32 Mbps \*After IP extension is enabled, the AI Function (SMD) will be disabled.
- Audio / Video:Encoding Capacity: Main stream: 5 MP Mode: 1-ch 5 MP@(1 fps-6 fps); others 5M-N@(1 fps-12 fps) 5M-N Mode: 5M-N@(1 fps –12 fps); 4M-N/1080p@(1 fps–15 fps); 1080N/720p/960H/D1/CIF@(1 fps–25/30 fps) Sub stream: D1/CIF@(1 fps–15 fps)
- Audio / Video:Dual-Stream: Yes
- Audio / Video:Video Bit Rate: 32 kbps–6144 kbps
- Audio / Video:Audio Sampling: 8 kHz, 16 bit
- Audio / Video:Audio Bit Rate: 64 kbps
- Audio / Video:Video Output: 1 HDMI, 1 VGA HDMI: 1920 × 1080, 1280 × 1024, 1280 × 720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720
- Audio / Video:Multi-Screen Display: When IP extension mode not enabled: 1/4 When IP extension mode enabled: 1/4/6

- Audio / Video:Third-party Camera Access: Panasonic; Sony; Hanwha; Axis; Arecont; ONVIF
- Compression Standard:Video Compression: AI Coding; Smart H.265+; H.265; Smart H.264+; H.264
- Compression Standard:Audio Compression: G.711a; G.711u; PCM
- Network:Network Protocol: HTTP; HTTPS; TCP/IP; IPv4; IPv6; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; FTP; DDNS; SNMP; Alarm Server; P2P; Auto Registration; IP Search (Supports IP camera, DVR, NVS, etc.)
- Network:Mobile Phone Access: iOS; Android
- Network:Interoperability: ONVIF 22.12 (Profile T; Profile S; Profile G); CGI; SDK
- Network:Browser: Chrome; IE; Safari; Edge; Firefox
- Recording Playback:Record Mode: General; alarm; motion detection
- Recording Playback:Recording Playback: 1/4
- Recording Playback:Backup Method: USB device and network
- Recording Playback:Playback Mode: Instant playback; general playback; event playback; tag playback; smart playback
- Alarm:General Alarm: Motion detection; HDCVI alarm; camera external alarm; network alarm; PIR alarm
- Alarm:Anomaly Alarm: Error (no disk, disk error, low space, low quota space; network disconnection; IP conflict; MAC conflict); video loss; video tampering; camera offline
- Alarm:Intelligent Alarm: SMD Plus
- Alarm:Alarm Linkage: Record; snapshot (panoramic); IPC external alarm output; audio; buzzer; log; preset; email
- Ports:Audio Input: 1-channel RCA 4-channel BNC (Coaxial Audio)
- Ports:Audio Output: 1-channel RCA
- Ports:Two-Way Talk: Yes (share the same audio input with the first channel)
- Ports:HDD Interface: 1 SATA port, up to 16 TB. This limit varies depending on the environment temperature.
- Ports:USB: 2
- Ports:HDMI: 1
- Ports:VGA: 1
- Ports:Network Port: 1
- General:Power Supply: 12 VDC, 1.5 A
- General:Power Consumption: <4 W (without HDD)
- General:Weight: 0.55 kg (1.21 lb)
- General:Dimensions: 197.0 mm × 203.1 mm × 41.5 mm (7.76" × 8.00" × 1.63") (W × D × H)
- General:Operating Temperature: −10 °C to +45 °C (+14 °F to +113 °F)
- General:Storage Temperature: −20 °C to +60 °C (−4 °F to +140 °F)
- General:Installation: Desktop
- General:Certifications: CE-LVD: IEC 62368-1:2014 CE-EMC: EN IEC 61000-3-2:2019, EN 61000-3-3:2013+A1:2019, EN 55032:2015+A11:2020, EN 55035:2017+A11:2020, EN 55024:2010+A1:2015, EN 50130-4:2011+A1:2014 FCC: 47 CFR Part 15, Subpart B
- :Color: Black