



John Deere Tractor 3036E

Model No: JD-3036E-WRT



Price:

Rs. 5,014,999

Warranty:

1 Years(s) manufacturer warranty.
1 Year Or 1500 Hours.

Delivery:

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

Specifications:

- Name: John Deere Tractor 3036E
- Type: Tractors
- Engine - Engine Power (kW): 97/68/EC at engine rpm: 26.9 (36.6) @ 2500
- Engine - PTO Bhp: kW(hp): 22 (30)
- Engine - Rated RPM: 2500
- Engine - No Of Cylinders: 3
- Engine - Air Cleaner: Dry type w/ safety element and restriction indicator light
- Drivetrain: Transmission - Gear: NA | Transmission - Hydro: Hydro two-pedal automatic | Max. Speed, km/h (mph): 24 (15) | Clutch eHST: No | Clutch PowrReverser: N/A | Brakes: Wet Disc | Steering: Power Steering | Differential lock: Standard | 4-Wheel Drive: Standard
- Transmission - Differential Lock: Standard
- Transmission - Brakes: Wet Disc
- Hydraulic System: Type: Open Centre | Total Flow, l/min: 35.2 | Implement, l/min: 20.2 | Steering, l/min: 15
- PTO: Type: Independant | Location: Standard rear | Speed: 540 rear
- Hitches: Cat 13-point hitch: Standard | Lift capacity at lift points, kg: 946 | Lift capacity 610mm (24") behind lift ends, kg: 615
- Tyres: Turf - R3 - Front: 27x8.5-15 6PR | Turf - R3 - Rear: 41x14-20 6PR | Industrial - R4 - Front: 25x8.5-14 6PR | Industrial - R4 - Rear: 15-19.5 6PR | AG - R1 - Front: 7-14 6PR | AG - R1 - Rear: 11.2-24 6PR
- Fuel / Fuel Tank: 24 L
- Safety / Protection: ROPS/Cab: Complies with ASAE, OSH Standards | Driver safety system - PTO brake: Standard | Driver safety system - Operator present: Standard
- Dimensions: Total length with 3-point hitch, mm: 2820 | Total width, mm: 1434 | Height with ROPS, mm: 2322
- Overall Dimensions - Wheel base, mm: 1525
- Weight: Total permissible weight, kg: 2000 | Front axle, kg: 800 | Rear axle, kg: 1200 | Towing capacity, kg: 2500

Date: 2025-05-29 12:47