

### John Deere Tractor With Rotavator JD-5045D-WRT

Model No: JD-5045D-WRT



#### **Price:**

Rs. 7,500,000

### Warranty:

1 Years(s) manufacturer warranty.

1 Year Or 1000 Hours.

# **Delivery:**

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

## **Specifications:**

- Type: Tractors
- Capacity / Power: 45HP
- Clutch Type: Dual Cluch
- Single / Tandem Pump: Tandem
- Engine Engine Power (kW): kW (bhp) (At Rated Speed): 437.57 (44.6)
- Engine PTO Bhp: kW (bhp) (At Rated Speed): 370.86 (37.8)
- Engine Rated RPM: 2300
- Engine Cooling System: Coolant Cooled, With Overflow Reservoir Tank
- Engine Low Idle, RPM: 850 (-50/+ 25)
- Engine High Idle, RPM: 2500 (-25+50)
- Engine FIP: Mico Bosch Inline
- Engine Muffler: Underhood
- Engine Fuel Shut-Off: Manual, Lockable
- Engine Air Cleaner: 15 cm (6") Dry
- Engine Radiator: Core 48mm Al
- Engine Water Separator: Applicable
- Transmission Clutch Type: Collar Shift
- Transmission No Of Speeds: 8F+ 4R
- Transmission PTO: Standard 540 At 2200 ERPM/ 540E @ 1705RPM
- Transmission Final Reduction: Inboard Planetary
- Transmission Differential Lock: Standard
- Transmission Brakes: Wet Disc Brakes
- Hitches Three Point Linkage, Cat: Cat 2
- Hitches Lift Capacity At Hitch Points (Kg-f): 1400
- Hitches Sway Bar / Chain: Chain
- Wheels / Axle/Support Rear Tyre Size: 14.9\*28 (Normal)/14.9x28(HLD)
- Wheels / Axle/Support Wheel Fixing Arrangement: M20 Stud
- Wheels / Axle/Support Front Tyre Size: 8 x 18 (Normal) / 8x18 (HLD)
- Electricals Battery: One, 12V, 88Ah
- Electricals Alternator: 40 Amp
- Electricals Starter: 12 V, 2.5 KW
- Electricals Rear Work Lamp: Standard
- Electricals Pin Connector: Standard
- Electricals Head Lamp: 60/55 W H-4 bulb (LHT)
- Electricals Park Lamp & Tail Lamp: 5W, 21/5W
- Electricals Neutral Safety Switch: PTO Lever
- Electricals Turn Signal Light: 21 W
- Seat: Make: Harita, Sliding, Normal Comfort, Standard Seat Belt
- Fuel / Fuel Tank: 60 L
- Capacities Engine Sump (lit): 6.5
- Capacities Transmission (lit): 37
- Capacities Hydraulics (lit): Common To Transmission
- Capacities Cooling System (lit): 9.5
- Overall Dimensions Wheel base, mm: 1950

- Overall Dimensions Front Wheel Track, mm: 1420
- Overall Dimensions Rear Wheel Track, mm: 1420
- Overall Dimensions Turning Radius (w/o Brakes): 3.2
- Overall Dimensions Turning Radius (with Brakes): 3
- Overall Dimensions Tractor Weight, Kg (Front): 787
- Overall Dimensions Tractor Weight, Kg (Rear): 1188
- Overall Dimensions Tractor Weight, Kg (Total): 1975
- Overall Dimensions Ground Clearance (At Drop Box): 365mm

Date: 2025-11-03 18:15